

# **GEM/MONTANA ROYALE INSTALLATION INSTRUCTIONS**

## **4 Sided Frame**

Builders opening required 420mm wide by 570mm high (4 sided)  
With the base of the opening a minimum of 300mm from the floor.

The wall fixing plate and outer frame are supplied fixed together, first separate the 2 items by unscrewing the 6 self-tapping screws.

Secure the wall fixing plate to the wall using the screws and plugs supplied ensuring it is level and flat against the wall (alternative fixings may be required if plugs supplied are not suitable). Vent holes at the bottom.

Seal the wall fixing plate opening to the wall.

Fix black angled bracket to front of fire tray using 2 self-tappers supplied (not required on Montana model).

Install the fire into the wall fixing plate using foam seals and fixing screws provided.

Re-fit outer frame to wall fixing plate using the 6 self-tapping screws.

Fix 2 trims and ash pan cover to outer frame (magnets are fixed to outer frame)

Set up and commission gas fire using gas fire installation instructions.

### **FIXING KIT SUPPLIED**

3 off 10mm thick foam strips 600mm long

6 off screws and plugs

6 off self tapping screws

## **3 Sided Frame**

The wall fixing plate and outer frame are supplied fixed together, first separate the 2 items by unscrewing the 6 self-tapping screws.

The 3-sided fits into a standard opening of 410mm wide by 560mm high

The backing plate is fixed to the wall or marble using either double-sided tape (not supplied) Or screws and plugs supplied, once fitted the plate must be sealed.

Fix black angled bracket to front of fire tray using self-tappers supplied (not required on Montana model)

Install the fire into the backing plate using the foam seals and tie wire kit supplied.

Re-fit outer frame to wall fixing plate using the 6 self-tapping screws.

Fix 2 trims and ash pan cover to outer frame (magnets are fixed to outer frame)

Set up and commission gas fire using gas fire installation instructions.

### **FIXING KIT SUPPLIED**

3 off 10mm thick foam strips 600mm long

6 off screws and plugs

Tie wire fixing kit

2 off self tapping screws